

# CS4K Pro

## Media Server

---

Specification V1.1



## Contents

Overview.....	2
Features.....	2
Application scenarios.....	2
Hardware.....	4
Device specification.....	5
Dimensions.....	6
Packing list.....	7

Version	Release Date	Description
V1.0	Feb, 2021	Initial release.
V1.1	Aug, 2022	Added packing list.

## Overview

CS4K Pro is a professional media server with powerful playback and control capabilities, high stability, and great scalability. Based on robust hardware, it is optimized for media playback of two 4K videos. With the built-in GrandShow, a professional playback and control software, the server is capable of decoding and playing different formats of contents. Specially, various styles of screens can be realized, such as screen split, special-shaped screen splicing and recombination, etc. In addition, other features are also supported including multi-scene preset, and seamless switching between scenes, and more. All these capabilities and functions can greatly meet the demands from the video playback and control.

## Features


- Supports 2x DP1.4 outputs
- Supports up to 8192×2160@60Hz pixel-to-pixel display
- Supports playing various contents such as videos, images, PPT files, texts, etc.
- Supports edit, preview, switching, saving, and copying of multiple scenes.
- Supports functions such as freeze, background image display and scene switching
- Supports screen split and recombination for resolution within 8192×2160 to achieve the display on ultra-long screens
- Supports display content rotation at any angle and color adjustment
- Supports PVW mode for program edit and PGM mode for output contents monitoring
- Supports capturing of NDI or capture card
- Supports decoding and playback of HDR video
- Supports system restoration
- Supports time-limited authorization (custom)
- Supports timed power on or off, as well as automatic scene touring
- Supports Pad control for visualized operations, such as screen monitoring and scene switching
- Supports control via third party devices for scene switching, screen adjustment and volume adjustment, etc.

## Application scenarios




## Hardware

### Front



No.	Item	Description
1	USB port	2×USB 3.0 ports.
2	Power switch	Power on or off.

### Rear



No.	Item	Description
1	AC 100-240V	AC power port
2	PS/2	1x PS/2 keyboard port (purple), 1x PS/2 mouse port (green)
3	USB	2x USB 3.0 ports (blue), 2x USB 2.0 ports
4	VGA	1x VGA output port
5	COM	1x COM port
6	RJ45	1x LAN (RJ45) port
7	DVI	1x DVI output
8	HDMI1.4	1x HDMI 1.4 output
9	Audio	3.5mm audio input and output port

10	Mini DisplayPort 1.4	2x Mini DisplayPort 1.4 outputs
----	----------------------	---------------------------------

## Device specification


Model		CS4K Pro
Chassis		2U
Operation interface port		1x HDMI1.4/1x DVI (up to 3840×2160@30Hz)
Operation System		Windows 10 Professional
CPU		Intel® 6 cores, 12 threads
RAM		16G
SSD		500G M.2 high speed SSD
Video capture card (optional)		SDI, DVI port
Graphics card		Quadro® professional Graphics
Video output		2x Mini DisplayPort 1.4
Maximum resolution		8192 x 2160@60Hz
Audio		3.5mm audio input and multichannel output
Network bandwidth		1000M
Software		GrandShow
Operating environment	Temperature	0°C~45°C/32°F~113°F
	Humidity	10%RH~80%RH, non-condensing
Storage environment	Temperature	0°C~50°C/32°F~122°F
	Humidity	10%RH~90%RH, non-condensing
Electrical specification	Power supply	AC 100-240V, 50/60Hz
	Power	165W
Physical specification	Net weight	7.14kg/15.74lbs
	Dimensions (W×H×D)	482.6mm×98.0mm×391.7mm

## Dimensions

Unit: mm

Tolerance:  $\pm 0.1\text{mm}$

Chassis:



## Packing List


No.	Name	Qty.
1	CS4K Pro Media Server	1PCS
2	GrandShow software kit	1PCS
3	DP cable	2PCS
4	HDMI cable	1PCS
5	Power cord	1PCS
6	Keyboard and mouse kit	1PCS
7	DP to DVI connection cord	2PCS
8	Product Certification	1PCS
9	Warranty card	1PCS



## Legal notice

Copyright © 2023 Colorlight Cloud Technology Co., Ltd. All rights reserved.

Without the express written permission of Colorlight Cloud Technology Co., Ltd., no unit or individual may copy, transcribe or translate part or all of the contents of this book. Not to be used for any commercial or profit-making purposes in any form or by any means.

 **Colorlight**® logo is a registered trademark of Colorlight Cloud Technology Co., Ltd.

Without the written permission of the company or the trademark owner, no unit or individual may in any way or for any reason use, reproduce, modify, disseminate, transcribe or infringe all or any part of the above-mentioned trademark, nor may it be bundled with other products selling.

As factors such as product batches and production processes may change, in order to provide accurate product information, specification parameters, and product characteristics to match the actual product, the text description and picture effects in the document will be appropriately adjusted and revised. If it is necessary to carry out the above modification and adjustment without prior notice, please refer to the actual product.

Thank you for purchasing the product of Colorlight Cloud Tech Ltd. If you encounter any problems during use or have any suggestions, please contact us through official channels. We will do our best to provide support and listen to your valuable suggestions. You can visit [www.colorlightinside.com](http://www.colorlightinside.com) to get more updated information.

Service Phone

**4008 770 775**

### Colorlight Cloud Technology Co., LTD

Official Website: [www.colorlightinside.com](http://www.colorlightinside.com)  
Head Office Address: Room 37F-39F, Building 8, Zone A,  
Shenzhen International Innovation Valley, Vanke Cloud City, Dashi Yilu,  
Nanshan District, Shenzhen, China

